

S.C. TOP GEOCART S.R.L. – Distribuitorul Autorizat in Romania al Leica Geosystems



Bucuresti - Sediul Central
Str. Prof. Ion Maiorescu, Nr. 67, Sect. 2
Tel: 021.253.05.30; Fax: 021.252.12.15;
web: www.topgeocart.ro

- when it has to be right



LEICA BLK360

REALITY CAPTURE. NOW.



LEICA BLK360

IMAGING LASER SCANNER



GENERAL

Imaging scanner 3D scanner with integrated high-speed HDR spherical imaging system and Visual Inertial System (VIS) for real-time pre-registration

IMAGING

Camera system 13 Mpixel 4-camera system captures 104 Mpx raw data for calibrated 360° x 270° spherical image

DESIGN & PHYSICAL

Housing	Black anodized aluminium
Dimensions	Height: 155 mm Diameter: 80 mm
Weight	0.75 kg (0.85 kg incl. battery)
Transport cover	GVP739 Transportation cover
Mounting mechanism	Button-press quick release

Speed

< 8 sec. for full spherical LDR image at any light conditions

< 20 sec. for full spherical 5-brackets HDR image at any light conditions

OPERATION

Stand-alone operation	One-button operation
Mobile devices	BLK Live app for iOS and Android smartphones Leica Cyclone FIELD 360 app for iOS and Android tablet computers and smartphones
Wireless communication	Integrated wireless LAN (802.11 b/g/n)
Internal memory	Storage for up to 1500 setups
Instrument orientation	Upright and upside down

PERFORMANCE

Data acquisition < 20 sec. for complete full dome scan and spherical LDR image at 50 mm @ 10 m resolution with automatic tilt measurements

3D point accuracy* 4 mm @ 10 m

Real time pre-registration Automatic point cloud alignment based on real time tracking of scanner movement between setups based on Visual Inertial System (VIS) by video-enhanced inertial measurement unit

POWER

Battery type	Internal, rechargeable Li-Ion battery (Leica GEB825)
Capacity	Up to 70 setups per battery

ENVIRONMENTAL

Robustness	Designed for indoor and outdoor use
Operating temperature	0° C to + 40° C
Dust/Humidity	Solid particle/liquid ingress protection IP54 (IEC 60529)

SCANNING

Distance measurement system	High speed time of flight enhanced by Waveform Digitizing (WFD) technology
Laser class	1 (in accordance with IEC 60825-1:2014)
Wavelength	830 nm
Field of view	360° (horizontal) / 270° (vertical)
Range*	min. 0.5 m - up to 45 m
Point measurement rate	up to 680.000 pts/sec
Measurement modes	4 user selectable resolution settings (6/12/25/50 mm @ 10 m)

DATA PROCESSING

Data transfer	Wireless and USB 3.0
Desktop software	Leica Cyclone REGISTER 360 and Cyclone REGISTER 360 (BLK Edition)
Cloud software	HxDR Digital Reality: cloud-based digital reality platform

* At 78% albedo
All specifications are subject to change without notice.
All accuracy specifications are one sigma unless otherwise noted.
Copyright Leica Geosystems AG, Heerbrugg, Switzerland 2022.

